

TABLE 2 Tolerances on Openings of USA Standard Specifications for Industrial Perforated Plate and Screens

Perforated Opening			Tolerance on Openings	
Standard (metric), mm	USA Industrial Standard, in.	Additional Sizes, in.	Standard (metric), mm	
125.0	5		±2.5	± 0.100
		41/2		± 0.090
106.0	41/4		±2.1	± 0.085
100.0	4		± 2.0	± 0.080
		33/4		± 0.075
90.0	31/2		± 1.8	± 0.070
		31/4	• • •	± 0.065
75.0	3		± 1.5	± 0.060
	* * *	23/4		± 0.055
63.0	21/2		± 1.3	± 0.050
	•••	21/4	• • •	± 0.045
53.0	21/8		±1.1	± 0.043
50.0	2	···	± 1.0	± 0.040
	40/	1 7/8		± 0.038
45.0	13/4	 4 <i>5 1</i>	± 0.9	± 0.035
	 	1 5/8		± 0.033
37.5	11/2	40/	± 0.8	± 0.030
	 	1 3/8		± 0.028
31.5	11/4	43/	± 0.6	± 0.025
		1 3/ ₁₆	• • •	± 0.024
 5	11/	1 ½	 ⊥∩ =	± 0.023
26.5 25.0	1 ¹ / ₁₆		±0.5 ±0.5	± 0.021
25.0		15/ ₁₆	± 0.5	±0.020 ±0.019
22.4	7/ ₈	'716	 +0.46	
22.4	'/8	13/ ₁₆	± 0.46	±0.018 ±0.016
19.0	3/4	716	±0.38	± 0.015
13.0	74	11/ ₁₆		± 0.013 ± 0.014
16.0	5/8	/16	±0.32	± 0.014
10.0	70	9/16		± 0.012
13.2	17/32	710	±0.30	± 0.012
12.5	1/2		±0.28	± 0.012
12.0	/ _	15/32		± 0.011
11.2	7/16	/32	±0.28	± 0.011
9.5	3/8	• • •	±0.28	± 0.011
8.0	5/ ₁₆	•••	±0.26	± 0.010
6.7	17/ ₆₄	•••	±0.25	± 0.009
6.3	1/4	• • •	±0.25	± 0.009
5.6	7/ ₃₂		±0.23	± 0.009
4.75	3/16		±0.24 ±0.21	± 0.003
4.73	5/ ₃₂	•••	± 0.21 ± 0.19	± 0.003
	0.127 (1/8)		±0.19	± 0.007
	J / / / / /	•••		